



TreeSteamer©-Mini Model by ScoringAg

Specifications for TreeSteamer©-Mini

- 4 gal. per min. boiler fired by #2 low sulfur diesel
- 12 volt system with or without generator
- 2- steam/hot water lances with 20 ft hoses
- 50% hot water/steam system
- 1-200 gallon hopper style water supply tank
- 1 high pressure pump with engine with low pressure 12 volt surge pump
- 1-2 wheel steel bed trailer with ball hitch
- Can be pulled by ATV, UTV or small tractor
- Temperature and pressure gauges

Operating specifications for TreeSteamer©-Mini

- Uses No. 2 low sulfur diesel fuel with dial in temperature control
- Stainless steel construction
- Cat 66 Direct drive hi pressure 3000 psi pump
- 12 volt battery for low pressure water surge pump and fuel burner operation
- Hopper water tank for operation in hilly terrain or citrus ditches
- Low profile narrow trailer for citrus grove operation
- All materials built for hot water/wet steam operation
- One year warranty on all parts (except for freezing of unit)

**The TreeSteamer©-Mini is made to operate in groves that have a high amount of resets, buck-horned citrus trees and extra large and tall trees mixed together.
It also can be used to treat backyard citrus.**

Price upon request

ScoringAg, Inc. Copyright April 9, 2015

ScoringAg, Inc.

967 N Doral Ln, Venice, Florida 34293 USA

Fax: +1-941-497-3449

Phone: +1-941-497-3400

Email: Info@ScoringAg.com